

Adaptor ISO-KF / ISO-CF

INFICON ISO-KF fittings are manufactured according to ISO 2861/1, DIN 28403 and Pneurop 6606. Our quality fittings are the standard components for all vacuum and high vacuum applications. The high quality INFICON components are designed and tested for leak rates less than 1 x 10-9 mbar l/s.



BENEFITS

- Competitively priced
- World wide logistics
- Design and measures follow strictly international respected standards
- Surface finish, welds, material specifications and cleanliness meet or exceed high vacuum specifications
- 2011/65/EU RoHS compliant

ORDERING INFORMATION

DN 16 ISO- DN 25 ISO- DN 40 ISO- DN 25 ISO- DN 40 ISO- DN 40 ISO-KF / 16 CF-F KF / 16 CF-F KF / 16 CF-F KF / 40 CF-F KF / 63 CF-F

Transition piece DN 100 CF/40 ISO-

KF

Type

Transition piece, inox, DN 16CF /

16KF

Transition piece, inox, DN 16CF /

25KF

Transition piece, inox, DN 40CF /

16KF

Transition piece, inox, DN 40CF /

25KF

Transition piece, inox, DN 40CF /

40KF

Transition piece, inox, DN 63CF /

40KF

213-252

213-251

213-254

213-255

213-256

213-259

SPECIFICATIONS

Туре	DN 16 ISO- KF / 16 CF-F	DN 25 ISO- KF / 16 CF-F	211 10 100		DN 40 ISO- KF / 40 CF-F	DN 40 ISO- KF / 63 CF-F
Dimension A	35	35	30	30	50	35
Dimension B	16	16	16	26	37	41
Material	Stainless Steel 304L / 1.4306					

DN 40 ISO-KF / 100 CF-F

213-262

SPECIFICATIONS

Туре	DN 40 ISO- KF / 100 CF- F		
Dimension A	50		
Dimension B	41		
Material	Stainless		
	Steel 304L /		
	1.4306		



