

FPM Seal CF

INFICON CF quality fittings are manufactured according to ISO 3669 and the latest TS/ ISO 3669-2 standard. INFICON Ultra high vacuum fittings are designed for applications down to 1×10^{-12} mbar and bakeout temperatures up to 400°C.



BENEFITS

- World wide logistics
- 2011/65/EU RoHS compliant


ORDERING INFORMATION


Type	DN 16 CF	DN 40 CF	DN 63 CF	DN 100 CF	DN 160 CF	DN 200 CF
Viton seal DN 100 CF, 2 pcs.				213-394		
Viton seal DN 16 CF, 5 pcs.	213-391					
Viton seal DN 160 CF, 2 pcs.					213-395	
Viton seal DN 200 CF, 2 pcs.						213-396
Viton seal DN 40 CF, 5 pcs.		213-392				
Viton seal DN 63 CF, 2 pcs.			213-393			

SPECIFICATIONS

Type	DN 16 CF	DN 40 CF	DN 63 CF	DN 100 CF	DN 160 CF	DN 200 CF
Dimension A	2	2.5	3.2	3.2	3.2	3.2
Dimension B	21	48.2	82.7	119.8	171.1	222.5
Dimension C	16	42	69.7	107.8	156	206
Dimension D			2.5	2.5	2.5	2.5
Set of:	5 pcs.	5 pcs.	2 pcs.	2 pcs.	2 pcs.	2 pcs.
Material:	FPM	FPM	FPM	FPM	FPM	FPM

DIMENSIONS





www.inficon.com reachus@inficon.com

Due to our continuing program of product improvements, specifications are subject to change without notice.
RateWatcher is a trademark of INFICON. All other trademarks are the property of their respective owners.

(2014-09) © 2014 INFICON