

Protective Lids

INFICON ISO-K quality fittings are manufactured according to ISO 1609, DIN 28404 and Pneurop 6606. Our quality large diameter fittings are the standard vacuum components for all vacuum and high vacuum lines. The high quality INFICON fittings are designed and tested for leak rates less than 1×10^{-9} mbar l/s.



BENEFITS

- Competitively priced
- World wide logistics
- 2011/65/EU RoHS compliant

ORDERING INFORMATION

Type	DN 63 ISO-K	DN 100 ISO-K	DN 160 ISO-K	DN 200 ISO-K	DN 250 ISO-K	DN 320 ISO-K
Protective lid DN 100 ISO-K		212-312				
Protective lid DN 160 ISO-K			212-313			
Protective lid DN 200 ISO-K				212-314		
Protective lid DN 250 ISO-K					212-315	
Protective lid DN 320 ISO-K						212-316
Protective lid DN 400 ISO-K						
Protective lid DN 500 ISO-K						
Protective lid DN 63 ISO-K	212-311					
Protective lid DN 630 ISO-K						

DN 400 ISO- DN 500 ISO- DN 630 ISO-
K K K

212-317


212-318

212-319

SPECIFICATIONS

Type	DN 63 ISO-K	DN 100 ISO-K	DN 160 ISO-K	DN 200 ISO-K	DN 250 ISO-K	DN 320 ISO-K
Dimension A	102	137	187	248	297.5	380
Dimension B	95	130	180	240	290	370
Dimension C	18	18	18	18.5	18.5	23.5
Material:	Polyethylene	Polyethylene	Polyethylene	Polyethylene	Polyethylene	Polyethylene

DIMENSIONS



SPECIFICATIONS

Type	DN 400 ISO- K	DN 500 ISO- K	DN 630 ISO- K
Dimension A	461	557	697
Dimension B	450	550	690
Dimension C	23.5	24	29
Material:	Polyethylene	Polyethylene	Polyethylene



www.inficon.com reachus@inficon.com

Due to our continuing program of product improvements, specifications are subject to change without notice.
RateWatcher is a trademark of INFICON. All other trademarks are the property of their respective owners.

(2014-09) © 2014 INFICON