

PGD500

The INFICON Pirani Gauge Display PGD500 in combination with the INFICON Pirani Standard Gauge PSG5xx provides a cost effective pressure monitoring solution.

Although it is called Pirani Gauge Display the PGD500 also supports our PCG55x and MPG series vacuum gauges.



ADVANTAGES

- User selectable measurement unit (Pa, mbar or Torr)
- Compact bench top model design can be easily mounted in a panel or 19" rack
- 0 to 10 V output signal from the gauge is available for use in PLC or with a chart recorder
- One free adjustable set point
- CE certified

ORDER INFORMATION

Туре	PGD500
PGD500 Pirani Gauge Display	398-802

SPECIFICATIONS

OI LOII IOATIONO		
Туре		PGD500
Measurement channels		1 (PSG5xx, PCG5xx or MPG series)
Display		LCD
Range	Pa	5×10⁻⁻ 1.5×10⁵
Range	mbar	5×10⁻° 1500
Range	Torr	3.75x10 ⁻⁹ ?????? 1125
Measurement rate	1/s	30
Measurement unit (selectable)		Pa, mbar, Torr
Setpoint		
Setpoint relay		1
Adjustment range (depending on gauge)		1×10⁻⁵ 500
Hysteresis		≥10% of measurement value
Relay contact		floating changeover contact
Connector		D-Sub, 9-pole, male
Setpoint		
Contact rating	V (ac)	50
Setpoint		
Contact rating	A (ac)	5
Analog output	V	0 10.3, sensor output signal
Power		
Supply	V (ac)	100 240
Power		
Frequency	Hz	50 60
Power		
Consumption	VA	≤30
Temperature		
Operation (ambiance)	°C	+5 +50
Storage	°C	–20 60
Relative humidity		≤80% up to +31 °C, decreasing to 50% at +40 °C
Degree of protection		IP20
Weight	kg	0.85
	<u> </u>	

ACCESSORIES

	PGD500
Cable 1.3m/4.3ft, a, FCC_FCC, Cont	398-498
Centering ring with filter DN 16 KF	211-090
Rack mount front-Adapter 2HE/ 3HE	398-499

DIMENSIONS

DIMENSIONS



